

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.

12.

13.

14.

15.

16.

17.

18.

1

XXXXXXXXX (

1.1

1.2

1.3

1.4

1.5

1.6

1.7

1.8

ASME

ASME UV

ASME UV

1.9

inch Lb


SI

MPa

2

mm
(mm)

5.06MP



a

17

b

3.2



API 2000

API 527

ASTM A193

ASTM A194

ASTM A320

NACE MR-0103

ASTM A216

ASTM A182

6.1.1 ASME VIII

ASME VIII

6.1.2

6.1.3

6.1.4

6.1.5

6.1.6

6.1.7

6.1.8

6.2

6.2.1

6.2.2 ASME B16.5

6.2.3 ASME B16.5, Ra 125 250 AARH(3.2 6.3)

Ra 63 AARH (1.6)

6.3

ASME VIII

● ± 1%

● 10% 21%



7%

15%

7

7.1

7.1.1

7.1.2

7.1.3

7.1.4

()

7.1.5

7.2

24

7.3

Stellite

3mm

7.4

7.4.1

1 1/4Cr-1/2Mo

2 1/4Cr-1Mo

9Cr-1Mo-V

+

5Cr-1/2Mo

9Cr-1Mo

+

7.4.2

7.4.3

7.5

8

8.1 100%UT

8.2

8.2.1 ASME/ANSI B16.34

API 527

8.2.2

8.2.3 ASME PTC25

8.2.4 /

8.3

8.4

8.5

8.5.1 1 1/4Cr-1/2Mo 2 1/4Cr-1Mo 9Cr-1Mo-V + 5Cr-1/2Mo 9Cr-1Mo

+

8.5.2

-
-
-
-
-

13

13.1

13.2

13.3

13.4

24

24

14

14.1

2

3

14.2

				/		
1		1+1	1			*

2		1+1	1			*
3		1+1	1			*
4				7/1		
5	()			7/1		
6		1+1				
7				7/1		
8				7/1		
9				7/1		

-
-
-

18

0596-6311294/19959614208

84

363216

E-mail jjliu@fhcpec.com.cn

0 BOM